▲ <sup>®</sup> 速 能 化 工 貿 易 有 限 公 司

ULTRA ENERGY ADHESIVE TRADING CO. LTD.

香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel: 852-2751 8880 Fax: 852-2795 1625 Web Site: <u>www.uea.com.hk</u> E-mail: <u>info@uea.com.hk</u>

## **MATERIAL SAFETY DATA SHEET**

Issue date : 23 December 2009

# 1. Chemical Product and Company IdentificationProduct : Ethyl Cyanoacrylate AdhesiveRegion : Hong KongType : V100AContact Information :Company Address :Telephone : (852) 2751 8880Room 1009, 10/F., International Plaza, 20Emergency Telephone : (852) 2751 8880Sheung Yuet Road, Kowloon Bay, Kowloon, HongKong.

#### 2. Composition / Information on Ingredients

Hazardous Components	8	ACGIHTLV	OSHA PEL	OTHER
Ethyl Cyanoacrylate 7085-85-0	80 -100	0.2 ppm TWA	None	None

#### 3. Hazards Identification

Emergency Overview			
		HMIS:	
Physical	Liquid	HEALTH :	2
State :			
Color :	Clear Colorless	FLAMMABILITY :	2
Odor :	Sharp, Irritating	PHYSICAL HAZARD :	1
		Personal Protection :	See Section 8
WARNING :	MAY CAUSE EYE AND RESP	IRATORY IRRITATION.	
	BONDS SKIN IN SECONDS.		

#### Relevant routes of exposure : Skin, Inhalation, Eyes

Refevant fouces of exposure.	SKIII, IIIIIAIACIOII, EYES
Potential Health Effects	
Inhalation :	Exposure to vapors above the established exposure limit results in
	respiratory irritation which may lead to difficulty in breathing
	and tightness in the chest.
Skin contact :	Bonds skin in seconds. May cause skin irritation. Cyanoacrylates
	have been reported to cause allergic reaction but due to rapid
	polymerization at the skin surface, an allergic response is rare.
	Cyanoacrylates generate heat on solidification. In rare
	circumstances a large drop will burn the skin. Cured adhesive does
	not present a health hazard even if bonded to the skin.
Eye Contact :	Irritating to eyes. Causes excessive tearing. Eyelids may bond.
Ingestion :	Not expected to be harmful by ingestion. Rapidly polymerizes
	(solidifies) and bonds in mouth. It is almost impossible to swallow.
Existing conditions aggravated	
by exposure:	Skin, eye, and respiratory disorders.
4. First Aid Measures	
Inhalation :	Remove to open space with fresh air. Seek medical attention to treat
	symptomatically if discomfort persists.
Skin contact :	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel
	apart using a dull instrument. If skin is burned due to the rapid
	generation of heat by a large drop, seek medical attention. If lips

CA-V100A-MSDS-E - 1 -

are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.

### **していたい** <sup>®</sup> 速 能 化 工 貿 易 有 限 公 司 ULTRA ENERGY ADHESIVE TRADING CO. LTD.

香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel: 852-2751 8880 Fax: 852-2795 1625 Web Site: <u>www.uea.com.hk</u> E-mail: <u>info@uea.com.hk</u>

## MATERIAL SAFETY DATA SHEET

	lips apart with direct opposing force.
Eye Contact :	Immediately flush with plenty of water for at least 15 minutes. Get
	medical attention. If eyelids are bonded closed, release eyelashes
	with warm water by covering with a wet pad. Do not force eye open.
	Cyanoacrylate will bond to eye protein and will cause a lachrymatory
	effect which will help to debond the adhesive. Keep eye covered until
	debonding is complete, usually within 1 - 3 days. Medical attention
	should be sought in case solid particles of polymerized Cyanoacrylate
	trapped behind the eyelid caused abrasive damage.
Ingestion :	Ensure breathing passages are not obstructed. The product will
	polymerize rapidly and bond to the mouth making it almost impossible
	to swallow. Saliva will separate any solidified product in several
	hours. Prevent the patient from swallowing any separted mass.
Notes to physician :	Surgery is not necessary to separate accidentally bonded tissues.
	Experience has shown that bonded tissues are best treated by passive,
	non - surgical first aid. If rapid curing has caused thermal burns
	they should be treated symptomatically after adhesive is removed.
5. Fire - Fighting Meas	
Flash point :	80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup
Autoignition temperature :	485°C (905°F)

Flash point .	ou e (170 1) to ssid e (200 1) lagrable crosed cap
Autoignition temperature :	485°C (905°F)
Flammable / Explosive limits - lower % :	Not determined
Flammable / Explosive limits - upper % :	Not determined
Extinguishing media :	Dry powder. Foam. Water spray. Carbon dioxide.
Special fire fighting procedures :	Fire fighters should wear positive pressure self - contained
	breathing apparatus (SCBA).
Unusual fire or explosion hazards :	None
Hazardous combustion products :	Trace amounts of toxic and $/$ or irritating fumes may be
	released and the use of breathing apparatus is recommended.

6. Accidental Release Measures		
Environmental precautions :	Ventilate area.	
Clean - up methods :	Do not use cloths for mopping up. Flood with water to complete	
	polymerization and scrape off the floor. Cured material can	
	be disposed of as non - hazardous waste.	
7. Handling and Storage		
Handling : Storage :	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns. Keep in a cool, well ventilated area away from heat, sparks	
	and open flame. Keep container tightly closed until ready for use.	
Incompatible products :	No special restrictions on storage with other products.	
8. Exposure Controls / Perso	onal Protection	
Engineering controls :	Use positive down - draft exhaust ventilation if general	
	ventilation is insufficient to maintain vapor concentration	

CA-V100A-MSDS-E - 2 -

Respiratory protection :

below established exposure limits.

Use NIOSH approved respirator if there is potential to exceed

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.

 酸酸化工質易有限公司

 香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K.

 Tel: 852-2751 8880
 Fax: 852-2795 1625
 Web Site: www.uea.com.hk
 E-mail: info@uea.com.hk

# MATERIAL SAFETY DATA SHEET

exposure limit(s). Observe OSHA regulations for respiratory<br/>use (29 CFR 1910.134).Skin protection :Use nitrile gloves and aprons as necessary to prevent contact.<br/>Do not use PVC, nylon or cotton.Eye / Face protection :Chemical splash goggles or safety glasses with side shields.

#### 9. Physical and Chemical Properties

Physical state : Liquid Clear Colorless Color : Odor : Sharp, Irritating Odor Threshold : 1 -2 ppm Vapor pressure : Less than 0.5 mm Hg at 25°C (77°F) pH : Not applicable Greater than 149°C (300°F) Boiling point / range : Melting point / range : Not determined Specific gravity : 1.06 at 20°C Vapor density : Approximately 3 Evaporation rate : Not available Solubility in water : Polymerizes in presence of water Partition coefficient (n - octanol / Not determined water) : VOC content : Less than 2% ; 20g /L (California SCAQMD Method 316B) (estimated) 10. Stability and Reactivity

Stability :Stable under recommended storage conditionsHazardous polymerization :Rapid exothermic polymerization will occur in the presence<br/>of water, amines, alkalis and alcohols.Hazardous decomposition products :NoneIncompatability :Water, amines, alkalis and alcohols.Conditions to avoid :Spontaneous polymerization

#### 11. Toxicological Information

Product toxicity data :

Acute oral LD50 >5000mg /kg (rat) (estimated). Acute dermal LD50 >2000 mg /kg (rabbit) (estimated).

Carcinogen	Status
------------	--------

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA
Ethyl Cyanoacrylate 7085-85-0	No	No	No

#### Literature Referenced Target Organ & Other Health Effects

Health Effects Hazardous	Health Effects / Target Organs
Ethyl Cyanoacrylate	Allergen, Irritant, Respiratory
7085-85-0	

#### 12. Ecological Information

Ecological information : Not Known

CA-V100A-MSDS-E - 3 -

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.



香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel: 852-2751 8880 Fax: 852-2795 1625 Web Site: <u>www.uea.com.hk</u> E-mail: <u>info@uea.com.hk</u>

## **MATERIAL SAFETY DATA SHEET**

#### 13. Disposal Considerations

#### Information provided is for unused product only.

Recommended method of disposal :Dispose of in accordance with Federal, State and local<br/>regulations.EPA hazardous waste number :Not a RCRA hazardous waste.

#### 14. Transport Information

U.S. Department of Transportation Ground (49 CFR) : Proper shipping name : Combustible liquids, n.o.s. (Cyanoacrylate ester) Hazard class or division : Combustible liquid Identification number : NA 1993 Packing group : None (Not more than 450 Liters) Unrestricted Exceptions : Marine pollutant : None International Air Transportation (ICAO / IATA) : Proper shipping name : Aviation regulated liquids, n.o.s. (Cyanoacrylate ester) Hazard class or division : 9 Identification number : UN 3334 Packing group : None Exceptions : (Not more than 500ml) Unrestricted Water Transportation (IMO / IMDG) : Proper shipping name : Unrestricted Hazard class or division : None Identification number : None Packing group : None Marine pollutant : None 15. Regulatory Information United State Regulatory Information TSCA 8 (b) Inventory State : All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12 (b) Export Notification : None. CERCLA / SARA Section 302 EHS : None. CERCLA / SARA Section 311 / 312 : Immediate Health Hazard, Delayed Health Hazard, Fire, Reactive CERCLA / SARA Section 313 : None No California Proposition 65 listed chemicals are known to California Proposition 65 : be present. Canada Regulatory Information CEPA DSL / NDSL State : All components are listed on or are exempt from listing on the Domestic Substances List. WHMIS hazard class : B.3, D.2.B

CA-V100A-MSDS-E - 4 -

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.