MATERIAL SAFETY DATA SHEET

Issue date : 23 December 2009

1. Chemical Product and Company Identification

Product : Ethyl Cyanoacrylate Adhesive Region : Hong Kong
Type : CA906 Contact Information :

Company Address: Telephone: (852) 2751 8880

Room 1009, 10/F., International Plaza, 20 Emergency Telephone: (852) 2751 8880

Sheung Yuet Road, Kowloon Bay, Kowloon, Hong

Kong.

Composition / Information on Ingredients

Hazardous Components%ACGIHTLVOSHA PELOTHEREthyl Cyanoacrylate
7085-85-080 -1000.2 ppm TWANoneNone

3. Hazards Identification

Emergency Overview

<u>HMIS:</u>

Physical Liquid HEALTH: 2

State :

Color: Clear Colorless FLAMMABILITY: 2
Odor: Sharp, Irritating PHYSICAL HAZARD: 1

Personal Protection: See Section 8

WARNING: MAY CAUSE EYE AND RESPIRATORY IRRITATION.

BONDS SKIN IN SECONDS.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Exposure to vapors above the established exposure limit results in

respiratory irritation which may lead to difficulty in breathing

and tightness in the chest.

Skin contact: Bonds skin in seconds. May cause skin irritation. Cyanoacrylates

have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare.

Cyanoacrylates generate heat on solidification. In rare

circumstances a large drop will burn the skin. Cured adhesive does

not present a health hazard even if bonded to the skin.

Eye Contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes

(solidifies) and bonds in mouth. It is almost impossible to swallow.

Existing conditions aggravated

by exposure:

Skin, eye, and respiratory disorders.

4. First Aid Measures

Inhalation :

Remove to open space with fresh air. Seek medical attention to treat

symptomatically if discomfort persists.

Skin contact: Do not pull bonded skin apart. Soak in warm soapy water. Gently peel

apart using a dull instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull

CA-CA906-MSDS-E - 1 -

^{**} All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.

MATERIAL SAFETY DATA SHEET

lips apart with direct opposing force.

Eye Contact : Immediately flush with plenty of water for at least 15 minutes. Get

medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized Cyanoacrylate

trapped behind the eyelid caused abrasive damage.

Ingestion :
Ensure breathing passages are not obstructed. The product will

polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separted mass.

Notes to physician: Surgery is not necessary to separate accidentally bonded tissues.

Experience has shown that bonded tissues are best treated by passive, non - surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

5. Fire - Fighting Measures

Flash point : 80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup

Autoignition temperature: 485°C (905°F)

Flammable / Explosive limits - lower %: Not determined

Flammable / Explosive limits - upper %: Not determined

Extinguishing media: Dry powder. Foam. Water spray. Carbon dioxide.

Special fire fighting procedures : Fire fighters should wear positive pressure self - contained

breathing apparatus (SCBA).

Unusual fire or explosion hazards : None

Hazardous combustion products: Trace amounts of toxic and / or irritating fumes may be

released and the use of breathing apparatus is recommended.

6. Accidental Release Measures

Environmental precautions: Ventilate area.

Clean - up methods :
Do not use cloths for mopping up. Flood with water to complete

polymerization and scrape off the floor. Cured material can

be disposed of as non - hazardous waste.

7. Handling and Storage

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing

vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and

strong irritating vapors, and cause thermal burns.

Storage: Keep in a cool, well ventilated area away from heat, sparks

and open flame. Keep container tightly closed until ready for

use.

Incompatible products :
No special restrictions on storage with other products.

8. Exposure Controls / Personal Protection

Engineering controls: Use positive down - draft exhaust ventilation if general

ventilation is insufficient to maintain vapor concentration

below established exposure limits.

Respiratory protection : Use NIOSH approved respirator if there is potential to exceed

CA-CA906-MSDS-E - 2 -

^{**} All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.

MATERIAL SAFETY DATA SHEET

exposure limit(s). Observe OSHA regulations for respiratory

use (29 CFR 1910.134).

Skin protection: Use nitrile gloves and aprons as necessary to prevent contact.

Do not use PVC, nylon or cotton.

Eye / Face protection : Chemical splash goggles or safety glasses with side shields.

9. Physical and Chemical Properties

Physical state : Liquid

Color: Clear Colorless
Odor: Sharp, Irritating

Odor Threshold : 1 -2 ppm

Vapor pressure: Less than 0.5 mm Hg at 25°C (77°F)

pH : Not applicable

Boiling point / range : Greater than 149°C (300°F)

Melting point / range : Not determined Specific gravity : 1.05 at 20°C

Vapor density : Approximately 3

Evaporation rate : Not available

Solubility in water: Polymerizes in presence of water

Partition coefficient (n - octanol / Not determined

water) :

VOC content : Less than 2% ; 20g /L (California SCAQMD Method 316B)

(estimated)

10. Stability and Reactivity

Stability: Stable under recommended storage conditions

Hazardous polymerization : Rapid exothermic polymerization will occur in the presence

of water, amines, alkalis and alcohols.

Hazardous decomposition products : None

Incompatability : Water, amines, alkalis and alcohols.

Conditions to avoid : Spontaneous polymerization

11. Toxicological Information

Product toxicity data : Acute oral LD50 >5000mg /kg (rat) (estimated). Acute dermal

LD50 >2000 mg /kg (rabbit) (estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA
Ethyl Cyanoacrylate 7085-85-0	No	No	No

Literature Referenced Target Organ & Other Health Effects

Health Effects Hazardous	Health Effects / Target Organs
Ethyl Cyanoacrylate	Allergen, Irritant, Respiratory
7085-85-0	

12. Ecological Information

Ecological information : Not Known

MATERIAL SAFETY DATA SHEET

13. Disposal Considerations

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local

regulations.

EPA hazardous waste number : Not a RCRA hazardous waste.

14. Transport Information

U.S. Department of Transportation Ground (49 CFR) :

Proper shipping name: Combustible liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division : Combustible liquid

Identification number : NA 1993 **Packing group :** None

Exceptions: (Not more than 450 Liters) Unrestricted

Marine pollutant : None International Air Transportation (ICAO / IATA) :

Proper shipping name: Aviation regulated liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division: 9
Identification number: UN 3334
Packing group: None

Exceptions: (Not more than 500ml) Unrestricted

Water Transportation (IMO / IMDG) :

Proper shipping name : Unrestricted

Hazard class or division : None
Identification number : None
Packing group : None
Marine pollutant : None

15. Regulatory Information

United State Regulatory Information

TSCA 8 (b) Inventory State: All components are listed or are exempt from listing on the

Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None. CERCLA / SARA Section 302 EHS: None.

CERCLA / SARA Section 311 / 312 : Immediate Health Hazard, Delayed Health Hazard, Fire,

Reactive

CERCLA / SARA Section 313 : None

California Proposition 65 : No California Proposition 65 listed chemicals are known to

be present.

Canada Regulatory Information

CEPA DSL / NDSL State : All components are listed on or are exempt from listing on

the Domestic Substances List.

WHMIS hazard class : B.3, D.2.B