



# MATERIAL SAFETY DATA SHEET

Issue date : 23 December 2009

## 1. Chemical Product and Company Identification

**Product** : Ethyl Cyanoacrylate Adhesive **Region** : Hong Kong  
**Type** : CA980 **Contact Information** :  
**Company Address** : **Telephone** : (852) 2751 8880  
 Room 1009, 10/F., International Plaza, 20 **Emergency Telephone** : (852) 2751 8880  
 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong.

## 2. Composition / Information on Ingredients

Hazardous Components	%	ACGIHTLV	OSHA PEL	OTHER
Ethyl Cyanoacrylate 7085-85-0	80 -100	0.2 ppm TWA	None	None
Carbon Black 1333-86-4	1-5	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	None

## 3. Hazards Identification

### Emergency Overview

#### HMIS:

<b>Physical State</b> :	Liquid	<b>HEALTH</b> :	2
<b>Color</b> :	Black	<b>FLAMMABILITY</b> :	2
<b>Odor</b> :	Sharp, Irritating	<b>PHYSICAL HAZARD</b> :	1
<b>WARNING</b> :	MAY CAUSE EYE AND RESPIRATORY IRRITATION. BONDS SKIN IN SECONDS.		
		<b>Personal Protection</b> :	See Section 8

**Relevant routes of exposure** : Skin, Inhalation, Eyes

### Potential Health Effects

**Inhalation** : Exposure to vapors above the established exposure limit results in respiratory irritation which may lead to difficulty in breathing and tightness in the chest.

**Skin contact** : Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.

**Eye Contact** : Irritating to eyes. Causes excessive tearing. Eyelids may bond.

**Ingestion** : Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

**Existing conditions aggravated by exposure** : Skin, eye, and respiratory disorders.

## 4. First Aid Measures

**Inhalation** : Remove to open space with fresh air. Seek medical attention to treat symptomatically if discomfort persists.

**Skin contact** : Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a dull instrument. If skin is burned due to the rapid



## MATERIAL SAFETY DATA SHEET

generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.

**Eye Contact :**

Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1 - 3 days. Medical attention should be sought in case solid particles of polymerized Cyanoacrylate trapped behind the eyelid caused abrasive damage.

**Ingestion :**

Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.

**Notes to physician :**

Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non - surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

### 5. Fire - Fighting Measures

**Flash point :** 80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup  
**Autoignition temperature :** 485°C (905°F)  
**Flammable / Explosive limits - lower % :** Not determined  
**Flammable / Explosive limits - upper % :** Not determined  
**Extinguishing media :** Dry powder. Foam. Water spray. Carbon dioxide.  
**Special fire fighting procedures :** Fire fighters should wear positive pressure self - contained breathing apparatus (SCBA).  
**Unusual fire or explosion hazards :** None  
**Hazardous combustion products :** Trace amounts of toxic and / or irritating fumes may be released and the use of breathing apparatus is recommended.

### 6. Accidental Release Measures

**Environmental precautions :** Ventilate area.  
**Clean - up methods :** Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non - hazardous waste.

### 7. Handling and Storage

**Handling :** Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.  
**Storage :** Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.  
**Incompatible products :** No special restrictions on storage with other products.

### 8. Exposure Controls / Personal Protection

**Engineering controls :** Use positive down - draft exhaust ventilation if general



## MATERIAL SAFETY DATA SHEET

**Respiratory protection :** ventilation is insufficient to maintain vapor concentration below established exposure limits. Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respiratory use (29 CFR 1910.134).

**Skin protection :** Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

**Eye / Face protection :** Chemical splash goggles or safety glasses with side shields.

### 9. Physical and Chemical Properties

**Physical state :** Liquid  
**Color :** Black  
**Odor :** Sharp, Irritating  
**Odor Threshold :** 1 -2 ppm  
**Vapor pressure :** Less than 0.5 mm Hg at 25°C (77°F)  
**pH :** Not applicable  
**Boiling point / range :** Greater than 100°C (212°F)  
**Melting point / range :** Not determined  
**Specific gravity :** 1.06 at 20°C  
**Vapor density :** Approximately 3  
**Evaporation rate :** Not available  
**Solubility in water :** Polymerizes in presence of water  
**Partition coefficient (n - octanol / water) :** Not determined  
**VOC content :** Less than 2% ; 20g /L (California SCAQMD Method 316B) (estimated)

### 10. Stability and Reactivity

**Stability :** Stable under recommended storage conditions

**Hazardous polymerization :** Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

**Hazardous decomposition products :** None

**Incompatibility :** Water, amines, alkalis and alcohols.

**Conditions to avoid :** Spontaneous polymerization

### 11. Toxicological Information

**Product toxicity data :** Acute oral LD50 >5000mg /kg (rat) (estimated). Acute dermal LD50 >2000 mg /kg (rabbit) (estimated).

#### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA
Ethyl Cyanoacrylate 7085-85-0	No	No	No
Carbon Black 1333-86-4	No	Group 2B	Yes

#### Literature Referenced Target Organ & Other Health Effects

Health Effects Hazardous	Health Effects / Target Organs
Ethyl Cyanoacrylate 7085-85-0	Allergen, Irritant, Respiratory
Carbon Black	Respiratory, Some evidence of carcinogenicity

\*\* All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.



## MATERIAL SAFETY DATA SHEET

1333-86-4

### 12. Ecological Information

Ecological information : Not Known

### 13. Disposal Considerations

Information provided is for unused product only.

Recommended method of disposal : Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number : Not a RCRA hazardous waste.

### 14. Transport Information

#### U.S. Department of Transportation Ground (49 CFR) :

Proper shipping name : Combustible liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division : Combustible liquid

Identification number : NA 1993

Packing group : None

Exceptions : (Not more than 450 Liters) Unrestricted

Marine pollutant : None

#### International Air Transportation (ICAO / IATA) :

Proper shipping name : Aviation regulated liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division : 9

Identification number : UN 3334

Packing group : None

Exceptions : (Not more than 500ml) Unrestricted

#### Water Transportation (IMO / IMDG) :

Proper shipping name : Unrestricted

Hazard class or division : None

Identification number : None

Packing group : None

Marine pollutant : None

### 15. Regulatory Information

#### United State Regulatory Information

TSCA 8 (b) Inventory State : All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification : None.

CERCLA / SARA Section 302 EHS : None.

CERCLA / SARA Section 311 / 312 : Immediate Health Hazard, Delayed Health Hazard, Fire, Reactive

CERCLA / SARA Section 313 : None

California Proposition 65 : No California Proposition 65 listed chemicals are known to be present.

#### Canada Regulatory Information

CEPA DSL / NDSL State : All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class : B.3, D.2.B