密 能 化 工 貿 易 有 限 公 司

 ULTRA ENERGY ADHESIVE TRADING CO. LTD.

 香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K.

香港九龍灣常悅道 20 號壞球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel : 852-2751 8880 Fax : 852-2795 1625 Web Site : <u>www.uea.com.hk</u> E-mail : <u>info@uea.com.hk</u>

## MATERIAL SAFETY DATA SHEET

### 1. Identification

Product Name	:	Hot Melt Adh	esive	
Manufacturer's Code	:	385A		
Usage	:	Bookbinding,	hardcover books	, magazine

#### 2. Physical Properties

:	E.V.A. Copolymer
:	White flake or pellet
:	100%
:	5,000 CPS / 160°C
	3,600 CPS / 170°C
	2,550 CPS / 180°C
:	160°C – 180°C
:	90°C
:	3 - 5 Sec
:	Roller or sprayer
:	2 Years up
	::

### 3. Ingredients

Ingredients		CAS No.
E.V.A. Copolymer	:	24937 - 78 - 8
Hydrocarbon Resin	:	64742 - 16 - 1
Wax	:	8002 - 72 - 2
Antioxidant	:	6683 - 19 - 8

### 4. Safe Handling Information

Storage and transport	:	Store in cool, dry condition away from sources of heat, strong oxidizing agent.
Spills and disposal	:	If molten material is spilt, allow to cool then scrape up for disposal, wash area with water and detergent.
Reactivity data	:	Incompatible with strong oxidizing agent and will melt when heated.
Fire/Explosion hazard	:	Hazardous decomposition product on burning oxides of carbon, light flammable, smoke and other organic vapors. Fire fighting personnel to wear self contained breathing apparatus and protective clothing.
Extinguishing media	:	Water spray

### 5. Health Hazard Information

Health Effects:

No adverse effects expected if the product is handle in accordance with this

HMC-385A-MSDS-E - 1 -

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.



速能化工貿易有限公司

ULTRA ENERGY ADHESIVE TRADING CO. LTD.

香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel : 852-2751 8880 Fax : 852-2795 1625 Web Site : <u>www.uea.com.hk</u> E-mail : <u>info@uea.com.hk</u>

# MATERIAL SAFETY DATA SHEET

safety data sheet.

Acute Effect Swallowed Eyes Skin Inhaled	<ul> <li>s:</li> <li>Practically non-harmful</li> <li>Molten material will burn</li> <li>Molten material may cause thermal burn</li> <li>Practically non-harmful at ambient temperature, vapers at elevated temperature (above 250°C) may cause irritation to the eyes and respiratory tract due to decomposition products.</li> </ul>	
Chronic Effects: No Chronic effects		
Dinat Did.		
First Aid:		
Swallowed	: Seek medical advice.	
Eyes	: If molten material enters eye flush with cool running water, seek urgently medical attention.	
Skin	: If molten material contacts the skin, immediately immerse area in water or flush area with cool running water. Do not make any immediate attempt to remove adhesive form the skin. Once the area has cooled, wipe adhesive off using mineral oil, seek medical advice.	
Inhaled	: Remove victim to fresh air, seek medical attention if symptoms persist.	

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.