WITTER A MERCER A MERCER A MERCER ADHESIVE TRADING CO. LTD.

香港九龍灣常悅道 20 號環球工商大廈 10 樓 9 室 Room 9, 10/F. International Plaza, 20 Sheung Yuet Road, Kowloon Bay, H.K. Tel: 852-2751 8880 Fax: 852-2795 1625 Web Site: <u>www.uea.com.hk</u> E-mail: <u>info@uea.com.hk</u>

# **MATERIAL SAFETY DATA SHEET**

## 1. Identification

Product Name	:	Hot Melt Stick
Manufacturer's Code	:	125
Usage	:	Artcraft, Toy, Furniture, Woodworking,
		Packing, Assembling, etc.

### 2. Physical Properties

Basis	:	E.V.A. Copolymer
Appearance	:	Clear White Glue Stick
Solid content	:	100%
Viscosity	:	18,000 CPS / 160°C
		14,500 CPS / 170°C
		10,750 CPS / 180°C
Working temperature	:	85°C
Adhesion	:	2.0 kg / in
Open time	:	15 - 30 Sec
Working method	:	Glue Gun
Storage	:	2 Years up

### 3. Ingredients

Ingredients	CAS. NO.	010
E.V.A. Copolymer	24937 - 78 - 8	55%
Hydrocarbon Resin (Saturate)	64742 - 16 - 1	45%

#### 4. Safe Handling Information

Storage and transport	:	Store in cool, dry condition away from sources of heat, strong oxidizing agent.
Spills and disposal	:	If molten material is spilt, allow to cool then scrape up for disposal, wash area with water and detergent.
Reactivity data	:	Incompatible with strong oxidizing agent and will melt when heated.
Fire/Explosion hazard	:	Hazardous decomposition product on burning oxides of carbon, light flammable, smoke and other organic vapors. Fire fighting personnel to wear self contained breathing apparatus and protective clothing.
Extinguishing media	:	Water spray

#### 5. Health Hazard Information

Health Effects:

No adverse effects expected if the product is handle in accordance with this safety data sheet.

HMA-125-MSDS-E - 1 -

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.

Provide T 貿易有限公司
COLLTRA ENERGY ADHESIVE TRADING CO. LTD.
Tel: 852-2751 8880 Fax: 852-2795 1625 Web Site: www.uea.com.hk E-mail: info@uea.com.hk

# MATERIAL SAFETY DATA SHEET

Acute Effect	s:	
Swallowed	:	Practically non-harmful
Eyes	:	Molten material will burn
Skin	:	Molten material may cause thermal burn
Inhaled	:	Practically non-harmful at ambient temperature, vapers at elevated temperature (above $250^{\circ}$ C) may cause irritation to the eyes and respiratory tract due to decomposition products.
Chronic Effe	ect	: No Chronic effect
First Aid:		
Swallowed	:	Seek medical advice.
Eyes	:	If molten material enters eye flush with cool running water, seek urgently medical attention.
Skin	:	If molten material contacts the skin, immediately immerse area in water or flush area with cool running water. Do not make any immediate attempt to remove adhesive form the skin. Once the area has cooled, wipe adhesive off using mineral oil, seek medical advice.
Inhaled	:	Remove victim to fresh air, seek medical attention if symptoms persist.

<sup>\*\*</sup> All the information is provided on the basic in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. UEA and its agents, dealers, distributors, directors and employees cannot accept any liability for the results whatsoever arising from the use of UEA's products due that the utilization of these products is simply out of UEA's control. The users are responsible for selecting the suitability of the products and methods of use.